





# Standard Drum Sizes, Length Capacity, Volume, and Weight



## IMPERIAL DIMENSIONS

Cable			10	12	16	16	15	17.75	24	24	30	30	36	36	36	42	54	62	72	
Type	Weight (lbs/foot)	Diameter (inches)	F x W (inches)	10 x 9	12 x 9	16 x 9	16 x 9	15 x 9.75	17.75 x 15	24 x 11.5	24 x 14	30 x 14	30 x 14	36 x 14	36 x 14	36 x 26	42 x 26	54 x 26	62 x 26	72 x 36
			Drum Weight Only (lbs)	2.5	3	3	4	7	11	14	15	19	29	47	38	77	105	154	193	390
			Volume (Cu.Feet)	0.57	0.83	1.47	1.47	1.40	3.01	4.22	5.13	8.02	8.02	11.6	11.6	21.5	29.2	48.3	63.6	118.8
LMR-195	0.022	0.195	I	676	1197	1816	2822	2634	4909											
LMR-200	0.022	0.195	I	676	1197	1816	2822	2634	4909											
LMR-240	0.034	0.240	I	423	851	1125	1799	1695	3109	4672										
LMR-300	0.055	0.300	Maximum	295	499	720	1130	1093	1982	2906	3867	3627								
LMR-400	0.068	0.405	Cable		296	406	619	542	1110	1504	2166	2095	3403	3834						
LMR-500	0.097	0.500	Length			275	412	341	684	1042	1431	1214	2092	2616	3496	4931	3469			
LMR-600	0.131	0.590	Capacity						504	723	1024	904	1590	1743	2443	3249	2549			
TRC-500	0.213	0.720	per Reel								685	639	1030	1194	1579	2256	1487			
LMR-900	0.266	0.870	(feet)										717	789	1059	1473	977	3511	5070	
LMR-1200	0.448	1.200	I												616	796	525	1639	2744	4061
TRC-875	0.458	1.200	I												616	796	525	1639	2744	4061
LMR-1700	0.736	1.670	I															869	1252	2020
TRC-1250	0.765	1.670	I															869	1252	2020

**NOTE:** 1) cable length capacity per reel and reel sizes are a general guideline only and do not necessarily represent how specific lengths may be shipped.  
 2) capacity chart is applicable to all LMR types, including -DB, -FR, PVC, -LLPL, -UltraFlex.



## METRIC DIMENSIONS

Cable			254	305	406	406	381	451	610	610	762	762	914	914	914	1067	1372	1575	1829	
Type	Weight (KG/M)	Diameter (mm)	F x W (mm)	254 x 229	305 x 229	406 x 229	406 x 229	381 x 248	451 x 381	610 x 292	610 x 356	762 x 356	762 x 356	914 x 356	914 x 356	914 x 660	1067 x 660	1372 x 660	1575 x 660	1829 x 914
			Drum Weight Only (KG)	1.1	1.4	1.4	1.8	3.2	5.0	6.4	6.8	8.6	13.2	21.3	17.2	34.9	47.6	69.9	87.5	176.9
			Volume (Cu.meters)	0.016	0.023	0.042	0.042	0.040	0.085	0.119	0.145	0.227	0.227	0.327	0.327	0.607	0.827	1.367	1.802	3.364
LMR-195	0.033	4.95	I	206	365	553	860	803	1496											
LMR-200	0.033	4.95	I	206	365	553	860	803	1496											
LMR-240	0.051	6.10	I	129	259	343	548	517	948	1424										
LMR-300	0.082	7.62	Maximum	90	152	219	344	333	604	886	1179	1105								
LMR-400	0.101	10.29	Cable		90	124	189	165	338	459	660	639	1037	1169						
LMR-500	0.144	12.70	Length			84	125	104	208	318	436	370	638	797	1066	1503	1057			
LMR-600	0.195	14.99	Capacity						154	220	312	276	485	531	745	990	777			
TRC-500	0.317	18.29	per Reel							209	195		314	364	481	687	453	1503		
LMR-900	0.396	22.10	(meters)										219	240	323	449	298	1070	1545	
LMR-1200	0.667	30.48	I												188	243	160	499	837	1238
TRC-875	0.682	30.48	I												188	243	160	499	837	1238
LMR-1700	1.095	42.42	I															265	382	616
TRC-1250	1.139	42.42	I															265	382	616

**NOTE:** 1) cable length capacity per reel and reel sizes are a general guideline only and do not necessarily represent how specific lengths may be shipped.  
 2) capacity chart is applicable to all LMR types, including -DB, -FR, PVC, -LLPL, -UltraFlex.