

News release

Times Microwave Systems expands its offering of LMR[®] Advantage[™] X-Series connectors

Times Microwave Systems introduces over 90 new connectors for the LMR[®] family with an emphasis on the LMR[®]-195 and LMR[®]-240 cable families. With many new interfaces and configurations, Times will have the right connector for the job. The expanded offering contains both EZ (spring finger pin) and TC (solder-pin) designs. As with all Times connectors, the new models have excellent corrosion resistance, rugged pull strength and optimized VSWR performance.

All X-Series connectors are rated to IP-67 and are compatible with our WSB boots and CST prep tools. These connectors are easier and faster to install because they do not require braid-wire trimming.

The electrical performance of the X-Series connectors, with the simple termination process and the easy-to-use prep tools, make for quick, consistent, high quality terminations. You can trust the Times Microwave Systems' line of LMR[®] cable, Advantage[™] X Series connectors and CST prep tools to get the job done.



For questions contact:

Kevin Moyher: Product Manager

Tel.: +1 203 949 8447

Email: kevin.moyher@timesmicro.com

New Connectors

LMR[®]-100

PART NUMBER	DESCRIPTION
SZ-100-BM	BNC-Male (plug) crimp connector
SC-100-NF-BH	N-Female (jack) bulkhead crimp connector, solder pin
SC-100-SM-RA	SMA-Male (plug) right angle crimp connector
SC-100-MCXF	MCX-Female (plug) crimp connector
SC-100-SF	SMA-Female (jack) crimp connector
SC-100-TM	TNC-Male (plug) crimp connector
SC-100-SM	SMA-Male (plug) crimp connector



News release

LMR[®]-195

PART NUMBER	DESCRIPTION
<u>EZ-195-200-4310M-X</u>	4.3/10-male (plug) crimp connector, non-solder pin, no braid trim
<u>EZ-195-200-4310M-RA-X</u>	4.3/10-male (plug) right angle, crimp connector, non-solder pin, no braid trim
<u>EZ-195-200-716M-X</u>	7/16-male (plug) crimp connector, non-solder pin, no braid trim
<u>EZ-195-200-716M-RA-X</u>	7/16-male (plug) right angle, crimp connector, non-solder pin, no braid trim
<u>EZ-195-200-QNM-RA-X</u>	QN-male (plug) right angle, crimp connector, non-solder pin, no braid trim
<u>EZ-195-200-QNF-X</u>	QN-female (jack) crimp connector, non-solder pin, no braid trim
<u>EZ-195-NF-BH-X</u>	N-female (jack) bulkhead crimp connector, non-solder pin, no braid trim
<u>EZ-195-NMH-X</u>	N-male (plug) crimp connector, non-solder pin, no braid trim
<u>EZ-195-TM-X</u>	TNC-male (plug) crimp connector, non-solder pin, no braid trim
<u>EZ-195-TM-RP-X</u>	TNC-male (plug) reverse polarity crimp connector, non-solder pin, no braid trim
<u>EZ-195-200-NF-X</u>	N-female (jack) crimp connector, non-solder pin, no braid trim
<u>EZ-195-QM-X</u>	QMA-male (plug) crimp connector, non-solder pin, no braid trim
<u>EZ-195-QF-X</u>	QMA-female (plug) crimp connector, non-solder pin, no braid trim
<u>EZ-195-200-NF-BH-X</u>	N-female (jack) bulkhead, crimp connector, non-solder pin, no braid trim
<u>EZ-195-200-SF-X</u>	SMA-female (jack) crimp connector, non-solder pin, no braid trim
<u>EZ-195-200-TF-BH-X</u>	TNC-female (jack) bulkhead, crimp connector, non-solder pin, no braid trim
<u>EZ-195-200-UM-X</u>	UHF-male (plug) crimp connector, non-solder pin, no braid trim
<u>EZ-195-200-UM-RA-X</u>	UHF-male (plug) right angle, crimp connector, non-solder pin, no braid trim
<u>EZ-195-200-QNM-X</u>	QN-male (plug) crimp connector, non-solder pin, no braid trim
<u>TC-195-NMH-X</u>	N-Male (plug) crimp connector, no braid trim
<u>TC-195-NMH-RA-D</u>	N-Male (plug) crimp right angle connector
<u>EZ-195-SM-RA-X</u>	SMA-Male (plug) crimp connector, non-solder pin, right angle, no braid trim
<u>EZ-195-TF-RP-X</u>	TNC-female (jack) reverse polarity crimp connector, non-solder pin, no braid trim
<u>TC-195-TM-X</u>	TNC-Male (plug) crimp connector; no braid trim

LMR[®]-200

PART NUMBER	DESCRIPTION
<u>EZ-200-BF-X</u>	BNC-Female (plug) crimp connector, non-solder pin, no braid trim
<u>EZ-200-BM-X</u>	BNC-Male (plug) crimp connector, non-solder pin, no braid trim
<u>EZ-200-SM-X</u>	SMA-Male (plug) crimp connector, non-solder pin, no braid trim
<u>EZ-200-TM-X</u>	TNC-Male (plug) crimp connector, non-solder pin, no braid trim
<u>EZ-200-NMH-75-X</u>	N-Male (plug) crimp connector, non-solder pin, no braid trim
<u>EZ-200-FM-75-X</u>	F-Male (plug) crimp connector, non-solder pin, no braid trim
<u>TC-200-SM-RA-D</u>	SMA-Male (plug) right angle, crimp connector no braid trim

News release

LMR[®]-240

PART NUMBER	DESCRIPTION
EZ-240-4310M-RA-X	4.3/10-male (plug) right angle, crimp connector, non-solder pin, no braid trim
EZ-240-716M-RA-X	7/16-male (plug) right angle, crimp connector, non-solder pin, no braid trim
EZ-240-QNM-X	QN-male (plug) crimp connector, non-solder pin, no braid trim
EZ-240-QNM-RA-X	QN-male (plug) right angle, crimp connector, non-solder pin, no braid trim
EZ-240-QNF-X	QN-female (jack) crimp connector, non-solder pin, no braid trim
EZ-240-NF-BH-X	N-female (jack) bulkhead crimp connector, non-solder pin, no braid trim
EZ-240-BM-75-X	BNC-male (plug) crimp connector, non-solder pin, no braid trim
EZ-240-TM-PL-X	TNC-male (plug) crimp connector, non-solder pin, no braid trim
EZ-240-TM-RP-PL-X	TNC-Male (plug) crimp, reverse polarity (non-solder pin), no braid trim
TC-240-NMH-RA-D	N-male (plug) right angle, crimp connector, solder-on pin
EZ-240-TF-RP-X	TNC-Female (jack) crimp/reverse polarity, non-solder male pin, no braid trim
EZ-240-TM-X	TNC-male (plug) crimp connector, non-solder pin, no braid trim
TC-240-TM-X	TNC-male (plug) crimp connector, solder-on pin, no braid trim
TC-240-TM-RA-D	TNC-male (plug) right angle crimp connector, solder-on pin
EZ-240-NMH-75-X	N-male (plug) crimp connector, non-solder pin, no braid trim
EZ-240-TF-PL-X	TNC-female (jack) crimp connector, non-solder pin, no braid trim
EZ-240-SM-X	SMA-male (plug) crimp connector, non-solder pin, no braid trim
TC-240-BM-RA-D	BNC-male (plug) right angle, crimp connector, solder-on pin
EZ-240-FM-75-X	F-male (plug) crimp connector, non-solder pin, no braid trim
TC-240-NF-BH-X	N-Female (jack) crimp bulkhead connector, no braid trim
EZ-240-QM-X	QMA-Male (plug) crimp connector/non-solder; Quick Disconnect SMA, no braid trim
TC-240-SM-RA-SS-D	SMA-Male (plug) crimp right angle connector
EZ-240-SM-RA-X	SMA-Male (plug) crimp right angle connector (non-solder pin), no braid trim
EZ-240-QM-RA-X	QMA-Male (plug) crimp right angle/non-solder; Quick Disconnect SMA, no braid trim

LMR[®]-300

PART NUMBER	DESCRIPTION
EZ-300-4310M-X	4.3/10-male (plug) crimp connector, non-solder pin, no braid trim
EZ-300-716M-X	7/16-male (plug) crimp connector, non-solder pin, no braid trim
EZ-300-716M-RA-X	7/16-male (plug) right angle crimp connector, non-solder pin, no braid trim
EZ-300-NF-X	N-female (jack) crimp connector, non-solder pin, no braid trim



News release

LMR[®]-400

PART NUMBER	DESCRIPTION
EZ-400-4310M-X	4.3/10-Male (plug) crimp non-solder pin, no braid trim
EZ-400-4310M-RA-X	4.3/10-Male (plug) right angle crimp non-solder pin, no braid trim
EZ-400-TF-PL-X	TNC-Female (jack) crimp non-solder pin, no braid trim
EZ-400-TM-PL-X	TNC-Male (plug) crimp non-solder pin, no braid trim
EZ-400-QNM-X	QN-Male (plug) crimp non-solder pin, no braid trim
EZ-400-QNM-RA-X	QN-Male (plug) crimp right angle non-solder pin, no braid trim
EZ-400-QNF-X	QN-female (jack) crimp non-solder pin, no braid trim
EZ-400-NF-BH-X	N-female (jack) bulkhead crimp non-solder pin, no braid trim
EZ-400-NMH-75-X	N-Male (plug) crimp non-solder pin, no braid trim
EZ-400-NMK-X	N-Male (plug) crimp non-solder pin, no braid trim

LMR[®]-500

PART NUMBER	DESCRIPTION
EZ-500-4310M-X	4.3/10-Male (plug) crimp connector (non-solder pin), no braid trim
EZ-500-4310M-RA-X	4.3/10-Male (plug) right angle crimp connector (non-solder pin), no braid trim
EZ-500-716M-X	7/16-Male (plug) crimp connector (non-solder pin), no braid trim
EZ-500-716M-RA-X	7/16-Male (plug) right angle crimp connector (non-solder pin), no braid trim



LMR[®]-600

PART NUMBER	DESCRIPTION
EZ-600-4310M-X	4.3/10-male (plug) crimp connector, non-solder pin, no braid trim
EZ-600-4310M-RA-X	4.3/10-male (plug) right angle crimp connector, non-solder pin, no braid trim
EZ-600-QNM-RA-X	QN-male (plug) right angle crimp connector, non-solder pin, no braid trim
EZ-600-QNF-X	QN-female (jack) crimp connector, non-solder pin, no braid trim
EZ-600-SM-X	SMA-male (plug) crimp connector, non-solder pin, no braid trim
EZ-600-QNM-X	QN-male (plug) crimp connector, non-solder pin, no braid trim
EZ-600-FM-75-X	F-male (plug) crimp connector, non-solder pin, no braid trim
TC-600-716M-RA-D	7/16 DIN Male crimp right angle connector

LMR-900-DB and LMR-900-LLPX

PART NUMBER	DESCRIPTION
EZ-900-716FC-2-SP	7/16 DIN Female clamp connector, 2-piece design
EZ-900-716MC-2-SP	7/16 DIN Male clamp connector, 2-piece design
EZ-900-716MC-RA-2-SP	7/16 DIN Male clamp right angle connector, 2-piece design
EZ-900-NFC-2-SP	N-Female (jack) clamp connector, 2-piece design
EZ-900-NMC-2-SP	N-Male (plug) Clamp Connector, 2-piece design
EZ-900-78EIA-2-SP	7/8 EIA flange clamp connector, 2-piece design
EZ-900-78EIA-RA-2	7/8 EIA flange clamp right angle connector, 2-piece design

For additional details visit our website:

<https://www.timesmicrowave.com/Products/Connectors/>

About Times Microwave Systems

Times Microwave Systems has over 70 years of experience designing innovative, high-reliability, coaxial cables and assemblies for demanding interconnect applications. An engineering-oriented company specialized in high performance flexible and semi-rigid coaxial cables, connectors, and cable assemblies for RF transmission.